

## FST-951 Series Intelligent Addressable Heat Detectors

The NOTIFIER® FST-951 Series intelligent thermal detectors are designed for both performance and aesthetics, and are direct replacements for the FST-851 Series. A new modern, sleek, contemporary design and advanced thermal technologies make the FST-951 Series ideal for both system operation and building design. The point ID address, set using rotary decimal switches, provide specific detector locations.

The series includes a 135°F/57°C fixed-temperature, rate-of-rise, and a 190°F/88°C fixed high-temperature detectors. These thermal detectors provide effective, intelligent property protection in a variety of applications. Detectors are available for both FlashScan® and CLIP applications as designated.

### Features

#### SLC LOOP:

- Two-wire SLC loop connection
- Unit uses base for wiring

#### ADDRESSING:

- Addressable by device
- Rotary, decimal addressing  
(Refer to the *NOTIFIER panel manuals* for device capacity.)

#### ARCHITECTURE:

- Designed to meet UL 268 7th Edition
- Sleek, low-profile, stylish design
- State-of-the-art thermistor technology for fast response
- Integral communications and built-in device-type identification
- Built-in tamper resistant feature
- Built-in functional test switch activated by external magnet

#### OPERATION:

- Fixed temperature model (FST-951) factory preset to 135°F (57°C)
- Rate-of-rise model (FST-951R), 15°F (8.3°C) per minute
- High-temperature model (FST-951H) factory preset to 190°F (88°C)
- 360°-field viewing angle of the two visual alarm indicators, LEDs blink red in Normal condition and turn on steady red in Alarm
- LEDs blink every time the unit is polled

#### MECHANICALS:

- Sealed against back pressure
- SEMS screws for wiring of the separate base
- Designed for direct-surface or electrical-box mounting
- Plugs into separate base for ease of installation and maintenance
- Separate base allows interchange of photoelectric, ionization and thermal sensors

#### OTHER SYSTEM FEATURES:

- Remote test feature from the panel
- Walk test with address display
- Low standby current

#### OPTIONS:

- Remote LED output connection to optional RA100Z remote LED annunciator



### Installation

FST-951 Series plug-in intelligent thermal detectors use a detachable base to simplify installation, service and maintenance. Installation instructions are shipped with each detector.

Mount detector base (all base types) on an electrical backbox which is at least 1.5" (3.81 cm) deep. For a chart of compatible junction boxes, see *DN-60054*.

**NOTE:** Because of the inherent supervision provided by the SLC loop, end-of-line resistors are not required. Wiring "T-taps" or branches are permitted for Style 4 (Class "B") wiring only.

When using relay or sounder bases, consult the *ISO-X(A)* installation sheet I56-1380 for device limitations between isolator modules and isolator bases.

### Applications

Use thermal detectors for protection of property. For further information, refer to I56-6522, *Applications Manual for System Smoke Detectors*, which provides detailed information on detector spacing, placement, zoning, wiring, and special applications.

### Construction

These detectors are constructed of fire-resistant plastic. The FST-951 Series plug-in intelligent thermal detectors are designed to commercial standards and offer an attractive appearance.

### Operation

Each FST-951 Series detector uses one of the panel's addresses (total limit is panel dependent) on the NOTIFIER Signaling Line Circuit (SLC). It responds to regular polls from the control panel and reports its type and the status. If it receives a test command from the panel (or a local magnet test), it stimulates its electronics and reports an alarm. It blinks its LEDs when polled and turns the LEDs on when commanded by the panel. The FST-951 Series offers features and performance that represent the latest in thermal detector technology.

## Product Line Information

**NOTE:** “-IV” suffix indicates CLIP and FlashScan device.

**FST-951:** White, low-profile intelligent 135°F fixed thermal sensor, FlashScan only

**FST-951A:** Same as FST-951 but with ULC listing

**FST-951-IV:** Ivory, low-profile intelligent 135°F fixed thermal sensor, FlashScan and CLIP

**FST-951A-IV:** Same as FST-951-IV but with ULC listing

**FST-951R:** White, low-profile intelligent rate-of-rise thermal sensor, FlashScan only

**FST-951RA:** Same as FST-951 but with ULC listing

**FST-951R-IV:** Ivory, low-profile intelligent rate-of-rise fixed thermal sensor, FlashScan and CLIP

**FST-951RA-IV:** Same as FST-951R-IV but with ULC listing

**FST-951H:** White, low-profile intelligent 190°F fixed thermal sensor, FlashScan only

**FST-951HA:** Same as FST-951H but with ULC listing

**FST-951H-IV:** Ivory, low-profile intelligent 190°F thermal sensor, FlashScan and CLIP

**FST-951HA-IV:** Same as FST-951 but with ULC listing

### INTELLIGENT BASES

**NOTE:** For details on intelligent bases, see DN-60981.

**B300-6:** White, 6" base, standard flanged low-profile mounting base (CSFM: 7300-1653:0109)

**B300-6-IV:** Ivory, 6" base, standard flanged low-profile mounting base (CSFM: 7300-1653:0109)

**B300A-6:** Same as B300-6, ULC listed

**B300A-6-IV:** Ivory, 6" standard flanged low-profile mounting base, ULC listed

**B300-6-BP:** Bulk pack of B300-6, package contains 10

**B501-WHITE:** White, 4" standard European flangeless mounting base. UL/ULC listed (CSFM: 7300-1653:0109)

**B501-BL:** Black, 4" standard European flangeless mounting base. UL/ULC listed (CSFM: 7300-1653:0109)

**B501-IV:** Ivory color, 4" standard European flangeless mounting base. UL/ULC listed (CSFM: 7300-1653:0109)

**B501-WHITE-BP:** Bulk pack of B501-WHITE contains 10

**B224RB-WH:** White, relay base (CSFM: 7300-1653:0216)

**B224RB-IV:** Ivory, relay base (CSFM: 7300-1653:0216)

**B224RBA-WH:** White, relay base, ULC listing

**B224RBA-IV:** Ivory, relay base, ULC listing

**B224BI-WH:** White, isolator detector base (CSFM: 7300-1653:0216)

**B224BI-IV:** Ivory isolator detector base (CSFM: 7300-1653:0216)

**B224BIA-WH:** White, isolator detector base, ULC listing

**B224BIA-IV:** Ivory isolator detector base, ULC listing

**B200S-WH:** White, Intelligent addressable sounder base capable of producing sound output in high or low volume with ANSI Temporal 3, ANSI Temporal 4, continuous tone, marching tone, and custom tone. Uses FlashScan protocol. (CSFM: 7300-1653:0213)

**B200S-IV:** Ivory, Intelligent addressable sounder base capable of producing sound output in high or low volume with ANSI Temporal 3, ANSI Temporal 4, continuous tone, marching tone, and custom tone. Uses FlashScan protocol. (CSFM: 7300-1653:0213)

**B200SA-WH:** Same as B200S-WH, ULC listing

**B200SA-IV:** Same as B200S-IV, ULC listing

**B200SCOA-WH:** White, Intelligent, programmable sounder base in English/French (required in Canada for ULC applications with CO Series detector applications)

**B200SCOA-IV:** Ivory Intelligent, programmable sounder base in English/French (required in Canada for ULC applications with CO Series detector applications, ULC listing)

**B200S-LF-WH:** White, Low Frequency Intelligent, programmable sounder base. Produces a fundamental frequency of 520 Hz +/- 10% with a square wave or its equivalent; designed to meet the NFPA 72 sleeping space requirement. (CSFM: 7300-1653:0238)

**B200S-LF-IV:** Ivory, Low Frequency Intelligent, programmable sounder base. Produces a fundamental frequency of 520 Hz +/- 10% with a square wave or its equivalent; designed to meet the NFPA 72 sleeping space requirement. (CSFM: 7300-1653:0238)

**B200SR-WH:** White, Intelligent sounder base capable of producing sound output with ANSI Temporal 3 or continuous tone. Intended for retrofit applications. (CSFM: 7300-1653:0213)

**B200SR-IV:** Ivory, Intelligent sounder base capable of producing sound output with ANSI Temporal 3 or continuous tone. Intended for retrofit applications. (CSFM: 7300-1653:0213)

**B200SRA-WH:** Same as B200SR-WH with, ULC listing

**B200SRA-IV:** Same as B200SR-IV in Ivory color, ULC listing

**B200SR-LF-WH:** White, Low Frequency Intelligent, programmable sounder base. Produces a fundamental frequency of 520 Hz +/- 10% with a square wave or its equivalent; designed to meet the NFPA 72 sleeping space requirement. Intended for retrofit applications. (CSFM: 7300-1653:0238)

**B200SR-LF-IV:** Ivory, Low Frequency Intelligent, programmable sounder base. Produces a fundamental frequency of 520 Hz +/- 10% with a square wave or its equivalent; designed to meet the NFPA 72 sleeping space requirement. Intended for retrofit applications. (CSFM: 7300-1653:0238)

### MOUNTING KITS AND ACCESSORIES

**TR300:** White, replacement flange for B210LP(A) base

**TR300-IV:** Ivory, replacement flange for B210LP(A) base

**RA100Z(A):** Remote LED annunciator. 3-32 VDC. Mounts to a U.S. single-gang electrical box. For use with B501(A) and B300-6(A).

**M02-04-00:** Test magnet

**M02-09-00:** Test magnet with telescoping handle

**CK300:** Color Kit (includes cover and trim ring), white, 10-pack

**CK300-IV:** Color Kit (includes cover and trim ring), ivory, 10-pack

**CK300-BL:** Color Kit (includes cover and trim ring), black, 10-pack

## SPECIFICATIONS

---

**Sensitivity:** UL Applications: 0.5% to 4.0% per foot obscuration.  
ULC is 0.5% to 3.5%

**Size:** 2.0" (5.3 cm) high; base determines diameter

– **B300-6:** 6.1" (15.6 cm) diameter

– **B501:** 4" (10.2 cm) diameter

*For a complete list of detector bases see DN-60981*

**Shipping weight:** 3.4 oz. (95 g)

**Operating temperature range:**

- FST-951, FST-951R Series: –4°F to 100°F (–20°C to 38°C)
- FST-951H Series: –4°F to 150°F (–20°C to 66°C)

**Detector spacing:** UL approved for 50 ft. (15.24 m) center-to-center, FM approved for 25 x 25 ft. (7.62 x 7.62 m) spacing

**Relative humidity:** 10% – 93% non-condensing

**Thermal ratings:** fixed-temperature set point 135°F (57°C), rate-of-rise detection 15°F (8.3°C) per minute, high temperature heat 190°F (88°C)

**Mounting:** B300-6(A) flanged base, included

See “**Product Line Information: Intelligent Bases,**” if using a different base.

### ELECTRICAL SPECIFICATIONS

**Voltage range:** 15 - 32 volts DC peak

**Standby current (max. avg.):** 200µA @ 24 VDC (one communication every 5 seconds with LED enabled)

**Max current:** 4.5 mA @ 24 VDC (“ON”)

### Listings and Approvals

Listings and approvals below apply to the FST-951 Series detectors. In some cases, certain modules may not be listed by certain approval agencies, or listing may be in process. Consult factory for latest listing status.

- UL/ULC Listing: S747
- FM Approved
- CSFM: 7270-0028:0502



This document is not intended to be used for installation purposes.  
We try to keep our product information up-to-date and accurate.  
We cannot cover all specific applications or anticipate all requirements.  
All specifications are subject to change without notice.

### NOTIFIER

12 Clintonville Road  
Northford, CT 06472  
203.484.7161  
www.notifier.com

FlashScan® and NOTIFIER® are registered trademarks of Honeywell International, Inc.

©2019 by Honeywell International Inc. All rights reserved. Unauthorized use of this document is strictly prohibited.

Country of Origin: Mexico

