

IDP-PHOTO / IDP-PHOTO-T / IDP-PHOTOR

Intelligent Photoelectric Smoke Detector and Photoelectric Smoke Detector with Thermal

The IDP-PHOTO is a photoelectric smoke detector and the IDP-PHOTO-T is a photoelectric smoke detector with thermal. These plug in smoke detectors, with integral communication, provide features that surpass conventional detectors and are for use with the Honeywell Farenhyt Series fire alarm control panels (FACPs).

Detector sensitivity can be programmed from the FACP software. Sensitivity is continuously monitored and reported to the FACP. Point ID capability allows each detector's address to be set with rotary address switches, providing exact detector locations for selective maintenance when chamber contamination reaches unacceptable levels.

IDP-Photo and IDP-Photo-T have a unique optical sensing chamber that is engineered to sense smoke produced by a wide range of combustion sources. In the IDP-Photo-T, dual electronic thermistors add 135°F (57°C) thermal technology to maximize detection.

The IDP-PhotoR is a remote test capable detector for use with the DNR (W) duct smoke detectors. It is UL 268A listed when used with the DNR (W) duct smoke detector.

Installation

The IDP-Photo and IDP-Photo-T plug into a compatible IDP-series detector base. The IDP-PhotoR is a remote test capable detector for use with the DNR (W) duct smoke detector.



IDP-PHOTO (BASE NOT INCLUDED)

FEATURES & BENEFITS

- Sleek, low-profile design
- Superior EMI resistance for reliability
- Detector transmits signal to indicate maintenance is required
- Tamper-proof feature available on mounting bases
- MEA Listed 225-02-E Vol. V
- Reliable analog communications for trouble-free operation
- Simple field cleaning for code compliance
- Optional remote LED annunciator (System Sensor® PN RA100Z)
- Listed for use in duct applications
- Age resistant polymer housing
- Variety of mounting options to meet any application
- Plug-in mounting provides ease of installation
- Rotary address switches for fast installation
- Dual electronic thermistor design on the IDP-Photo-T
- Dual LED indicators for 360° visibility
- UL Listed
- FM Approved
- CSFM Listed

IDP-PHOTO, IDP-PHOTOR and IDP-PHOTO-T Technical Specifications

PHYSICAL

Height: 2.0" (5.08cm) less sensor

Diameter: 4.1" (10.4CM) installed in B501 base

ENVIRONMENTAL

Operating Temperature:

IDP-PHOTO: 32°F - 120 °F (0°C - 49°C)

IDP-PHOTO-T: 32°F - 100 °F (0°C - 38°C)

Humidity: 10 to 93% non-condensing)

ELECTRICAL RATINGS

Operating Voltage: 15 – 32VDC

SLC Standby and Alarm Current: 300 µA

OTHER RATINGS

IDP-PHOTO-T Thermal: Fixed temperature set point 135°F (57°C)

Velocity: 0 – 4000 fpm (0 – 20 m/sec) (suitable for installation in ducts)

IDP-PHOTO Insect Screen Hole Size: 0.016" (0.41 mm) nominal

ORDERING INFORMATION

IDP-PHOTO: Photoelectric Smoke Detector

IDP-PHOTO-T: Photoelectric Smoke Detector with Thermal (135°F)

IDP-PHOTOR: Photoelectric Smoke Detector, remote test capable, for use with DNR (W) duct smoke detector

ACCESSORIES

RA100Z: Remote LED Annunciator.

XR2B: Detector Removal Tool. A removal and replacement tool for IDP plug-in detectors. Includes the T55-127-000.

M02-04-01: Detector Test Magnet

M02-09-00: Test Magnet with Telescoping Handle

XP-4: Extension Pole for XR2B. Extends from 5 – 15 ft.

T55-127-000: Detector Removal Head.

BCK-200B: Black Detector Kit. For IDP-series detectors.

* Unless otherwise noted, specifications apply to IDP-Photo and IDP-Photo

COMPATIBILITY

The IDP-PHOTO, IDP-PHOTO-T and IDP-PHOTOR are compatible with the following IDP series detector bases:

- B210LP 6" Mounting Base
- B501 4" Mounting Base
- B224BI 6" Isolator Base
- B224RB 6" Relay Base
- B200SR 6" Sounder Base

The IDP-PHOTO, IDP-PHOTO-T and IDP-PHOTOR are compatible with the following Farenhyt Series FACP's:

- IFP-2100 / IFP-2100ECS / RFP-2100
- IFP-2000 / IFP-2000ECS / RPS-2000
- IFP-1000 / IFP-1000ECS
- IFP-300 / IFP-300ECS
- IFP-100 / IFP-100ECS
- IFP-75
- IFP-50

For a complete listing of all compliance approvals and certifications, please visit www.farenhyt.com.

Microsoft, Windows, and the Windows Logo are registered trademarks or trademarks of Microsoft Corporation.

Honeywell® is a registered trademark of and Farenhyt™ is a trademark of Honeywell International, Inc.

This document is not intended to be used for installation purposes. We try to keep our product information up-to date and accurate. We cannot cover all specific applications or anticipate all requirements. All specifications are subject to change without notice.

For Technical Support, Please call 800-446-6444.

For more information

Learn more about Honeywell's Farenhyt Series and other products available by visiting www.farenhyt.com

Honeywell Security & Fire

12 Clintonville Road
Northford, CT 06472
800-328-0103